

Force-H3



Maximum Scalability



Flexible & Easy Installation



Higher Density & Efficiency



Remote Maintenance



Module

2

3

4

5

6

7

Battery Module			FH10050				
Nominal Voltage (VDC)			102.4				
Battery Module Capacity (kWh)			5.12				
Battery System Capacity (kWh)		10.24	15.36	20.48	25.6	30.72	35.84
Usable Capacity (kWh)		9.69	14.73	19.48	24.32	29.17	34.01
Battery System Voltage(VDC)		204.8	307.2	409.6	512	614.4	716.8
Dimension (W*D*H mm)		540*350*530	540*350*700	540*350*870	540*350*1040	540*350*1210	540*350*1380
Weight (kg)		92	131	170	209	248	287
Depth of Discharge			95%				
Charge/ Discharge (A)	(Normal)	50					
	(Max)	55@15MIN					
Communication port			Modbus RTU/CAN				
Multi-group			Max 6 groups in parallel				
IP rating			IP55				
Working Temperature/ (°C) Charge			-10~55				
Storage Temperature/ (°C)			-20~45				
Humidity (RH)			5%~95% No condensation				
Altitude (m)			<4,000				
Design life (@25°C)			15+Years				
Cycle life (@25°C)			>8,000				
Certification		IEC62040-1/IEC62477-1/IEC62619/IEC63056/UL1973/UL9540A/UN38.3/VDE-AR-E 2510-50					

Swiss Distributor

ELEKTRON AG | Riedhofstrasse 11 | CH-8804 Au, ZH
T +41 44 781 04 64 | solar@elektron.ch | elektron.ch