



Hybrid Inverter 25-50kW

M2HT-25/29.9/30/40/50K-150

40A

Max. PV Input Current

100%

Unbalanced Output

150A

Max. Charge/Discharge

Commercial | Three Phase | HV Battery | 4 MPPTs



Enhanced Power & Performance

- 150% backup power @10s
- <10ms seamless on/off-grid switching
- 100% unbalanced load support
- Up to 200% grid input power support



Solar & Energy Optimization

- PV input current up to 20A
- 200% DC oversizing boosts efficiency
- High charging/discharging current
- Versatile applications for all scenarios



System Integration & Flexibility

- Parallel operation supports both off-grid and on-grid
- Half-wave load compatibility for stable performance
- Diesel generator integration secures reliable backup
- Third-party EMS & BMS compatibility



Intelligent Control & Maintenance

- 6 built-in operating modes optimize energy use
- Dynamic pricing mode maximizes cost efficiency
- Remote Upgrade Ensures Fast Updates
- Precise Export Limitation Prevents Grid Backfeed



Integ M Series

The Power Master

Distribution partner Switzerland

EN-M2HT-25-50-NO2.02-2025

©2025 Solinteg Power Co., Ltd. All rights reserved.

sales@solinteg.com

www.solinteg.com

ELEKTRON AG | Riedhofstrasse 11 | CH-8804 Au Zurich
T +41 44 781 04 64 | solar@elektron.ch | elektron.ch

Hybrid Inverter 25-50kW

Models		M2HT-25K-150	M2HT-29.9K-150	M2HT-30K-150	M2HT-40K-150	M2HT-50K-150
PV Side						
Max. PV Array Power	[kWp]	50	60	60	80	100
Max. PV Input Voltage *	[V]	1000*				
Rated PV Input Voltage	[V]	620				
Start-up Voltage	[V]	135				
MPPT Operating Voltage Range *	[V]	200-950*	200-950*	200-950*	200-950*	200-950*
No. of MPP Trackers		4	4	4	4	4
No. of Strings per MPPT		2/2/2/2	2/2/2/2	2/2/2/2	2/2/2/2	2/2/2/2
Max. Input Current per MPPT	[A]	40/40/40/40	40/40/40/40	40/40/40/40	40/40/40/40	40/40/40/40
Max. Short-circuit Current per MPPT	[A]	50/50/50/50	50/50/50/50	50/50/50/50	50/50/50/50	50/50/50/50
Battery Side						
Battery Type		Lithium-ion				
Battery Voltage Range	[V]	150-840				
No. of Battery Input		1				
Max. Charge/Discharge Current	[A]	150/150				
Max. Charge/Discharge Power	[kW]	25/25	30/30	30/30	40/40	50/50
Grid Side (On-Grid)						
Rated Output Power	[kW]	25.0	29.9	30.0	40.0	50.0
Max. Output Apparent Power	[kVA]	25.0	29.9	30.0	40.0	50.0
Rated AC Voltage	[V]	3L/N/PE; 220/380V; 230/400V; 240/415V				
Rated AC Frequency	[Hz]	50/60				
Rated Output Current	[A]	37.9/36.2/34.7	45.3/43.3/41.5	45.5/43.5/41.7	60.6/58/55.6	75.8/72.5/69.4
Max. Output Current	[A]	37.9	45.3	45.5	60.6	75.8
Power Factor		0.8 leading ...0.8 lagging				
THDi (@Rated Power)		<3%				
Max. Input Apparent Power **	[kVA]	50.0	59.8	60.0	80.0	80.0
Rated AC Voltage	[V]	3L/N/PE; 220/380V; 230/400V; 240/415V				
Rated AC Frequency	[Hz]	50/60				
Max. AC Input Current	[A]	75.8	90.6	90.9	121.2	121.2
Back-up Side (Off-Grid)						
Rated Output Power	[kW]	25.0	29.9	30.0	40.0	50.0
Peak Output Apparent Power	[kVA]	37.5 @10s	45 @10s	45 @10s	60 @10s	75 @10s
Rated Output Voltage	[V]	3L/N/PE; 220/380V; 230/400V; 240/415V				
Rated Output Frequency	[Hz]	50/60				
Rated Output Current	[A]	37.9/36.2/34.7	45.3/43.3/41.5	45.5/43.5/41.7	60.6/58/55.6	75.8/72.5/69.4
On/Off-grid Switching Time	[ms]	< 10ms				
THDv (@Linear Load)		<3%				
Generator Side						
Max. Input Apparent Power	[kVA]	25	29.9	30	40	50
Rated Input Voltage	[V]	3L/N/PE; 220/380V; 230/400V; 240/415V				
Rated Input Frequency	[Hz]	50/60				
Max. Input Current	[A]	37.9	45.3	45.5	60.6	75.8
Efficiency						
MPPT Efficiency		99.90%				
Max. Efficiency		97.80%				
European Efficiency		97.20%				
Max. Battery to AC Efficiency		98.50%				
Max. PV to Battery Efficiency		97.50%				
Protection						
Integrated Protection		DC reverse polarity protection / Battery input reverse connection protection / Insulation resistance protection / Surge protection(DC/AC: Type II/Type II) / Over-temperature protection / Residual current protection / Islanding protection / AC over-voltage protection / Overload protection / AC short-circuit protection				
General Data						
Dimensions	[W×H×D mm]	919*739*305				
Weight	[KG]	89				
Ingress Protection		IP66				
Standby Self-consumption	[W]	< 40				
Topology		Transformerless				
Operating Temperature Range	[°C]	-30~60				
Relative Humidity	[%]	0~100				
Max. Operation Altitude	[m]	3000				
Over Voltage Category		II(PV+Battery), III(Mains)				
Cooling		Smart Fan				
Noise Level	[dB]	< 65				
Display		LED & OLED				
Communication		CAN, RS485				

* PV Max. input voltage is 950V, otherwise inverter will be waiting;

** Max apparent power means the maximum power imported from the grid used to satisfy the backup loads and charge the battery;